



Specifications

- ◎ Collinear Load Test : 500x2kg,1200x2pounds
- ◎ Dual Voltage : 12 or 24 VDC(optional)
- ◎ The Standard Voltage is 12VDC when Finished
- ◎ MOV Provides Reverse Current Protection
- ◎ High Strength Material, Anodized Aluminum Housing
- ◎ Design without Mechanical Failure
- ◎ Increase the holding Force, Dual Insulative Housing
- ◎ Suitable For Wooden Door, Glass Door, Metal Door, Fireproof Door
- ◎ LED Indicates the Door Status
- ◎ Lock Status sensor(NO/NC/COM)
- ◎ Time: 0/3/6/9sec

Optional Accessories

- ◎ Lock Size : 530Lx74.7Wx38.5H(mm)
- ◎ Armature plate : 180Lx60Wx13H(mm)
- ◎ Holding Force : 500kgx2(1200Lbsx2)
- ◎ Voltage : DC12V or DC24V+10%
- ◎ Current Draw : 12V/420mAx2 24V/210mA
- ◎ Suitable for Wooden door, Glass door, Metal door, Fireproof door
- ◎ Surface Temp : $\leq +20^{\circ}\text{C}$
- ◎ Operating Temp : $-10\sim +55^{\circ}\text{C}$ (14-131F)
- ◎ Suitable Humidity : 0~95%(non-condensing)
- ◎ Finishes for Shell Anodized aluminum
- ◎ Finishes for Magnetic Zinc
- ◎ Finishes for Armature Zinc
- ◎ Signal Output Dry Contact,Max Rating of Contact Current 3A
- ◎ LED red indicates the door is unlock,Green indicates the door is lock
- ◎ Time : 0/3/6/9sec
- ◎ Weight : 9kg