



Specifications

- ⊙ Collinear Load Test : 180kgx2,350poundsx2
- ⊙ Dual Voltage : 12 or 24 VDC (optional)
- ⊙ The Standard Voltage is 12VDC when Finished
- ⊙ MOV Provides Reverse Current Protection
- ⊙ Anti-Residual Magnetism Designed
- ⊙ High Strength Material, Anodized Aluminum Housing
- ⊙ Design without Mechanical Failure
- ⊙ Increase the holding Force, Dual Insulative Housing

Optional Accessories

- ⊙ Lock Dimension : 400Lx39Wx21H(mm)
- ⊙ Armature Plate Dimension : 135Lx35Wx9.3H(mm)
- ⊙ Holding Force : 180kgx2(350Lbsx2)
- ⊙ Input Voltage : 12/24VDC+10%
- ⊙ Current Draw : 300mA_{x2} at 12VDC 150mA_{x2} at 24VDC
- ⊙ Suitable for Wooden door, Glass door, Metal door, Fireproof door
- ⊙ Surface Temp : ≤+20c
- ⊙ Operating Temp : -10~+55°C(14-131F)
- ⊙ Suitable Humidity : 0~95%(non-condensing)
- ⊙ Cover Finish Anodized aluminum
- ⊙ Lock Finish Zinc
- ⊙ Armature Plate Finish Zinc
- ⊙ Weight : 2.4KG