



Specifications

- ⊙ Collinear Load Test 280kgx2,600poundsx2
- ⊙ Dual Voltage 12 or 24 VDC (optional)
- ⊙ The Standard Voltage is 12VDC when Finished
- ⊙ MOV Provides Reverse Current Protection
- ⊙ Anti-Residual Magnetism Designed
- ⊙ High Strength Material, Anodized Aluminum Housing
- ⊙ Design without Mechanical Failure
- ⊙ Increase the holding Force, Dual Insulative Housing

Optional Accessories

- ⊙ Lock Dimension : 500Lx48.5Wx25H(mm)
- ⊙ Armature Plate Dimension : 160Lx38Wx11H(mm)
- ⊙ Holding Force : 280kgx2(600Lbsx2)
- ⊙ Input Voltage : 12/24VDC+10%
- ⊙ Current : 12V/500mA x2 24V/250mA x2 at 24VDC
- ⊙ Suitable Wooden door, Glass door, Metal door, Fireproof door
- ⊙ Surface Temp : ≤+20c
- ⊙ Operating Temp : -10~+55c(14-131F)
- ⊙ Humidity : 0~90%(non-condensing)
- ⊙ Cover Finish Anodized aluminum
- ⊙ Lock Finish Zinc
- ⊙ Armature Plate Finish Zinc
- ⊙ Weight : 4KG