



Specifications

- ⊙ Collinear Load Test : 500kg,1200pounds
- ⊙ Dual Voltage : 12 or 24 VDC(optional)
- ⊙ The Standard Voltage is 12VDC when Finished
- ⊙ MOV Provides Reverse Current Protection
- ⊙ High Strength Material, Anodized Aluminum Housing
- ⊙ Design without Mechanical Failure
- ⊙ Increase the holding Force, Dual Insulative Housing
- ⊙ Suitable For Wooden Door, Glass Door, Metal Door, Fireproof Door
- ⊙ LED Indicates the Door Status
- ⊙ Lock Status sensor(NO/NC/COM)

Optional Accessories

- ⊙ Lock Size : 265Lx74.7Wx38.5H(mm)
- ⊙ Armature plate : 180Lx60Wx13H(mm)
- ⊙ Holding Force : 500kgx2(1200Lbs)
- ⊙ Voltage DC12V or DC24V+10%
- ⊙ Current Draw 12V/420mAx2 24V/210mA
- ⊙ Suitable for Wooden door, Glass door, Metal door, Fireproof door
- ⊙ Surface Temp : $\leq +20^{\circ}\text{C}$
- ⊙ Operating Temp : $-10^{\circ}\text{C} \sim +55^{\circ}\text{C}$ (14-131F)
- ⊙ Suitable Humidity : 0~95%(non-condensing)
- ⊙ Finishes for Shell Anodized aluminum
- ⊙ Finishes for Magnetic Zinc
- ⊙ Finishes for Armature Zinc
- ⊙ Signal Output Dry Contact, Max Rating of Contact Current 3A
- ⊙ LED red indicates the door is unlock, Green indicates the door is lock
- ⊙ Weight : 4.5kg