



Specifications

- ◎ Collinear Load Test 280kg, 600pounds
- ◎ Dual Voltage 12 or 24 VDC (optional)
- ◎ The Standard Voltage is 12VDC when Finished
- ◎ MOV Provides Reverse Current Protection
- ◎ Suitable For Wooden Door, Glass Door, Metal Door, Fireproof Door
- ◎ LED Indicates the door Status
- ◎ Lock Status sensor(NO/NC/COM)
- ◎ Anti-Residual Magnetism Designed
- ◎ High Strength Material, Anodized Aluminum Housing
- ◎ Design without Mechanical Failure
- ◎ Increase the holding Force, Dual Insulative Housing

Optional Accessories

- ◎ Lock Dimension : 250Lx48.5Wx25H(mm)
- ◎ Armature Plate Dimension : 160Lx38Wx11H(mm)
- ◎ Holding Force : 280kg(600Lbs)
- ◎ Input Voltage : 12/24VDC+10%
- ◎ Current : 12V/500mA 24V/250mA
- ◎ Suitable Wooden door, Glass door, Metal door, Fireproof door
- ◎ Surface Temp : $\leq +20^{\circ}\text{C}$
- ◎ Operating Temp : $-10^{\circ}\text{C} \sim +55^{\circ}\text{C}$ (14-131F)
- ◎ Humidity : 0~90%(non-condensing)
- ◎ Cover Finish Anodized aluminum
- ◎ Lock Finish Zinc
- ◎ Armature Plate Finish Zinc
- ◎ Weight : 2KG